

GREASEMASTER

Compac

heavy duty compact grease pump

The greasemaster compac is designed as a simple but rugged grease pump which has the facility to adjust grease output. It is available in 12vdc and 24vdc versions.

The pump will accept up to 2 pumping elements and these are adjustable via the calibrating wheel with the yellow markers.

The integral impellor agitates the grease to keep it fluid and to expel air.

A rubber wiper cleans the reservoir and insures grease in the lower pumping chamber does not cavitate.

The pump will operate a progressive divider circuit to suit any small to medium machine.



Specification:

Capacity	2Kg Nominal reservoir size 5kg and 7.5kg also available
Grease Specification	Lithium NLGI 2
Voltage	12/24V
Motor Output Power	3.2W
Current Max	2A
Speed-12V	9RPM
Speed-24V	15RPM
Output Pressure	Adjustable up to 200bar
Delivery	Adjustable up to 0.25cc Per Min
Temperature Range	+40c -15c
Filling	1/8 bsp Port
Weight	4kg - full
Size	220w x 255h x 270d

GREASEMASTER
Compac

Trilube
Lubricating Solutions
PH:(02) 9820 5400

Website: www.trilube.com.au
Email: sales@trilube.com.au
Fax: (02) 9820 5411
Unit 1/17 Pembury Rd Minto NSW 2566